

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46

## Chapter 12 Suppression Chemicals & Delivery Systems

### Policy for Use of Fire Chemicals

Use only products qualified and approved for intended use. Follow safe handling procedures, use personal protective equipment recommended on the product label and *Material Safety Data Sheet* (MSDS).

A current list of qualified products and approved uses can be found on the Wildland Fire Chemical Systems (WFCS) website:

- <http://www.fs.fed.us/rm/fire/wfcs/index.htm>
- Link to appropriate Qualified Products List (QPL)

Refer to local jurisdictional policy and guidance related to use of wildland fire chemicals for protection of historic structures.

Products must be blended or mixed at the proper ratio prior to being loaded into the aircraft. Quality control and safety requirements dictate that mixing or blending of wildland fire chemicals be accomplished by approved methods.

### Types of Fire Chemicals

#### Long-Term Retardant

Long-term retardants contain fertilizer salts that change the way fuels burn. They are effective even after the water has evaporated. Retardants may be applied aerially by large air tanker, single engine airtanker (SEAT) and helicopter bucket. Some retardant products are approved for fixed tank helicopters. Some products are formulated specifically for delivery from ground sources. See the QPL for specific uses for each product.

Recommended coverage levels and guidelines for use can be found in the *10 Principles of Retardant Application*, NFES 2048, PMS 440-2 pocket card. Retardant mixing, blending, testing, and sampling requirements can be found at the WFCS website Lot Acceptance and Quality Assurance page: <http://www.fs.fed.us/rm/fire/wfcs/laqa.htm>.

#### Fire Suppressant Foam

Fire suppressant foams are combinations of wetting and foaming agents added to water to improve the effectiveness of the water. They are no longer effective once the water has evaporated. Foam may be applied by engines, portable pumps, helicopters and SEATs. Some agencies also allow application of foam from fixed-wing water scoopers. See the QPL for specific uses for each product.

1 **Wet Water**

2 Using foam concentrates at a mix ratio of 0.1 percent will produce a wet water  
3 solution.

4  
5 **Water Enhancer (Gel)**

6 Water enhancers, such as fire fighting gels, are added to water to improve the  
7 viscosity and adhesion of water. They are not effective once the water has  
8 evaporated. These products may be used in structure protection within the  
9 wildland interface or on wildland fuels. They are fully approved for use in  
10 helicopter bucket and engine application. Many are also approved, at specific  
11 mix ratios, for use in SEATs, and fixed tank helicopters. See the QPL for  
12 specific uses for each product.

13  
14 **Safety Information**

15  
16 **Personnel Safety**

17 All qualified wildland fire chemicals meet minimum requirements (June 2007)  
18 in regard to aquatic and mammalian toxicity (acute oral toxicity, acute dermal  
19 toxicity, primary skin irritation, and primary eye irritation). Specifications for  
20 long-term retardants, fire suppression foams, and water enhancers, can be found  
21 on the WFCS website.

22  
23 Personnel involved in handling, mixing, and applying fire chemicals or solutions  
24 shall be trained in proper procedures to protect their health and safety and the  
25 environment. Approved fire chemicals can be irritating to the eyes. Personnel  
26 must follow the manufacturer's recommendations; including use of PPE, as  
27 found on the product label and product MSDS. The MSDSs for all approved  
28 fire chemicals can be found on the web site at  
29 <http://www.fs.fed.us/rm/fire/wfcs/msds.htm>.

30  
31 Human health risk from accidental drench with fire chemicals can be mitigated  
32 by washing with water to remove any residue from exposed skin.

33  
34 Containers of any fire chemical, including backpack pumps and engine tanks,  
35 should be labeled to alert personnel that they do not contain only water and the  
36 contents are not potable.

37  
38 Slippery footing is a hazard at storage areas, unloading and mixing sites, and  
39 wherever applied. Because all fire chemical concentrates and solutions  
40 contribute to slippery conditions, all spills must be cleaned up immediately,  
41 preferably with a dry absorbent pad or granules. Firefighters should be aware  
42 that fire chemicals can conceal ground hazards. Wildland fire chemicals can  
43 penetrate and deteriorate leather boots, resulting in wet feet and potentially  
44 ruined leather.

45  
46

1 **Aerial Application Safety**

2 Personnel and equipment in the flight path of intended aerial drops should move  
3 to a location that will decrease the possibility of being hit with a drop.

4  
5 Personnel near aerial drops should be alert for objects (tree limbs, rocks, etc.)  
6 that the drop could dislodge. The Incident Response Pocket Guide (IRPG)  
7 provides additional safety information for personnel in drop areas.

8  
9 During training or briefings, inform all fire personnel of environmental  
10 guidelines and requirements for fire chemicals application and avoid contact  
11 with waterways.

12  
13 Avoid dipping from rivers or lakes with a helicopter bucket containing residual  
14 fire chemicals without first cleaning/washing down the bucket.

15  
16 Consider setting up an adjacent reload site and manage the fire chemicals in  
17 portable tanks or terminate the use of chemicals for that application.

18  
19 **Policy for Delivery of Wildland Fire Chemicals near Waterways**

20  
21 Avoid aerial application of wildland fire chemicals within 300 feet of waterways  
22 and any ground application of wildland fire chemicals into waterways. The  
23 policy has been adopted from the *2000 Guidelines for Aerial delivery of*  
24 *Retardant or Foam near Waterways* which were established and approved by  
25 the FS, BLM, NPS, and FWS. It has been expanded to include all wildland fire  
26 chemicals, including water enhancers.

27 This policy was updated in 2009 and can be found at.

28 [http://www.fs.fed.us/rm/fire/wfcs/Application\\_Policy-MultiAgency\\_042209-](http://www.fs.fed.us/rm/fire/wfcs/Application_Policy-MultiAgency_042209-UPDATE.pdf)  
29 [UPDATE.pdf](http://www.fs.fed.us/rm/fire/wfcs/Application_Policy-MultiAgency_042209-UPDATE.pdf)

30  
31 **Exceptions:**

- 32 • When alternative line construction tactics are not available due to terrain  
33 constraints, congested area, life and property concerns or lack of ground  
34 personnel, it is acceptable to anchor the wildland fire chemical application  
35 to the waterway. When anchoring a wildland fire chemical to a waterway,  
36 use the most accurate method of delivery in order to minimize placement of  
37 wildland fire chemicals in the waterway (e.g., a helicopter rather than a  
38 heavy airtanker).

39  
40 When potential damage to natural resources outweighs possible loss of aquatic  
41 life, the unit administrator may approve a deviation from these guidelines.

42  
43 **Definition of Waterway**

44 Any body of water including lakes, rivers, streams and ponds whether or not  
45 they contain aquatic life.

46

**1 Guidance for Pilots**

2 To meet the 300-foot buffer zone guideline, implement the following:

- 3 • **Medium/Heavy Airtankers:** When approaching a waterway visible to the  
4 pilot, the pilot shall terminate the application of wildland fire chemical  
5 approximately 300 feet before reaching the waterway. When flying over a  
6 waterway, pilots shall wait one second after crossing the far bank or shore  
7 of a waterway before applying wildland fire chemical. Pilots shall make  
8 adjustments for airspeed and ambient conditions such as wind to avoid the  
9 application of wildland fire chemical within the 300-foot buffer zone.
- 10 • **Single Engine Airtankers:** When approaching a waterway visible to the  
11 pilot, the pilot shall terminate application of wildland fire chemical  
12 approximately 300 feet before reaching the waterway. When flying over a  
13 waterway, the pilot shall not begin application of wildland fire chemical  
14 until 300 feet after crossing the far bank or shore. The pilot shall make  
15 adjustments for airspeed and ambient conditions such as wind to avoid the  
16 application of retardant within the 300-foot buffer zone.
- 17 • **Helicopters:** When approaching a waterway visible to the pilot, the pilot  
18 shall terminate the application of wildland fire chemical 300 feet before  
19 reaching the waterway. When flying over a waterway, pilots shall wait five  
20 seconds after crossing the far bank or shore before applying the wildland  
21 fire chemical. Pilots shall make adjustments for airspeed and ambient  
22 conditions such as wind to avoid the application of wildland fire chemicals  
23 within the 300-foot buffer zone.

24

25 This policy does not require the helicopter or airtanker pilot-in-command to fly  
26 in such a way as to endanger his or her aircraft, other aircraft, structures or  
27 compromise ground personnel safety.

28

**29 Reporting Requirements of Wildland Fire Chemicals into Waterways:**

30 Any fire chemicals aerially applied into a waterway or within 300 feet of a  
31 waterway require prompt upward reporting to incident management and agency  
32 administrator. Notifications will also be made for any spills or ground  
33 applications of fire chemicals into waterways or with potential to enter the  
34 waterway.

35

36 If it is believed that fire chemicals have been introduced into a waterway,  
37 personnel should immediately inform their supervisor. The incident or host  
38 authorities must immediately contact appropriate regulatory agencies and  
39 specialists within the local jurisdiction.

40

41 Initial notifications of wildland fire chemical mishaps will be reported as soon as  
42 possible to the WFCS Fire Chemical Project Leader in Missoula, Montana at  
43 phone 406-329-4859 (if no answer please leave message) or to individuals listed  
44 on website referenced below. Include the date, location, and extent of the  
45 mishap.

46

- 1 All information, including reporting form and instructions, are posted on the  
2 web site at: <http://www.fs.fed.us/rm/fire/wfcs/report.htm>.
- 3 • *FS - Additional Reporting Requirements for Threatened and Endangered*  
4 *Species. Reporting is also required for all introductions of wildland fire*  
5 *chemicals into habitat for those Threatened and Endangered species*  
6 *identified by the U.S Fish and Wildlife Service (FWS). The list and other*  
7 *information can be found at <http://www.fs.fed.us/fire/retardant/index.html>.*  
8 *This requirement resulted from the Forest Service's acceptance of*  
9 *Biological Opinions received from the National Marine Fisheries Service*  
10 *(NMFS) and the U.S. Fish and Wildlife Service (FWS). When wildland fire*  
11 *chemicals adversely affect any threatened, endangered, or proposed*  
12 *species, or designated or proposed critical habitat, regardless of the 300'*  
13 *waterway buffer zone, the Forest Service Line Officer must initiate*  
14 *emergency consultation with the FWS and/or NMFS. The FS unit should*  
15 *coordinate with the local FWS or NMFS office to monitor, determine*  
16 *significance of effects, and design appropriate responsive measures. The*  
17 *procedures, reporting form and instructions can be found at the same*  
18 *website as listed above.*

### 20 **Endangered Species Act (ESA) Emergency Consultation**

21  
22 The following provisions are guidance for complying with the emergency  
23 section 7 consultation procedures of the ESA with respect to aquatic species.  
24 These provisions do not alter or diminish an action agency's responsibilities  
25 under the ESA.

26  
27 Where aquatic threatened & endangered (T&E) species or their habitats are  
28 potentially affected by aerial application of wildland fire chemical, the following  
29 additional procedures apply:

- 30 • As soon as practicable after the aerial application of wildland fire chemical  
31 near waterways, determine whether the aerial application has caused any  
32 adverse effects to a T&E species or their habitat. This can be accomplished  
33 by the following:
- 34 ➤ Aerial application of wildland fire chemical outside 300 ft of a  
35 waterway is presumed to avoid adverse effects to aquatic species and  
36 no further consultation for aquatic species is necessary.
  - 37 ➤ Aerial application of wildland fire chemical within 300 ft of a  
38 waterway requires that the unit administrator determine whether there  
39 have been any adverse effects to T&E species within the waterway.
- 40 • These procedures shall be documented in the initial or subsequent fire  
41 reports:
- 42 ➤ If there were no adverse effects to aquatic T&E species or their  
43 habitats, there is no additional requirement to consult on aquatic species  
44 with Fish and Wildlife Service (FWS) or National Marine Fisheries  
45 Service (NMFS).

- 1       ➤ If the action agency determines that there were adverse effects on T&E  
2       species or their habitats then the action agency must consult with FWS  
3       and/or NMFS, as required by 50 CFR 402.05 (Emergencies).  
4       Procedures for emergency consultation are described in the *Interagency*  
5       *Consultation Handbook*, Chapter 8 (March, 1998). In the case of a  
6       long duration incident, emergency consultation should be initiated as  
7       soon as practical during the event. Otherwise, post-event consultation  
8       is appropriate. The initiation of the consultation is the responsibility of  
9       the unit administrator.  
10
- 11      Ground application of a wildland fire chemical into a waterway also requires  
12      determining whether the application has caused any adverse effects to a T&E  
13      species or their habitat. The procedures identified above also apply.  
14
- 15      Each agency is responsible for ensuring that their appropriate agency specific  
16      guides and training manuals reflect these standards.