

VIPR IBPA Resource Typing and Attributes Table

2026 Revision, edited by WO-FAM. Any questions or email comments to: sm.fs.vipr@usda.gov

Resource Category	Typing	Additional Resource Attributes <small>These attributes are listed on the DPL. If requested, preference will be given to the first available vendor, the attribute being requested.</small>
Water Handling	Tank Capacity Minimum Pump Flow(GPM)	Attributes
Engine	T3- 750 to 1500 gallons / 150 GPM T4- 750 to 1500 gallons / 50 GPM T5- 400 to 749 gallons / 50 GPM T6- 150 to 300 gallons / 50 GPM	4 wheel or All wheel drive required for Type 6 Engines. 4 wheel or AWD is an attribute for all other engines. CAFS: Compressed Air Foam System
Water Tender (Support)	T1 - 4000+ gallons / 300 GPM T2 - 2500 to 3999 gallons / 200 GPM T3 - 1000 to 2499 gallons / 200 GPM	All Wheel or 4 Wheel Drive
Water Tender (Tactical)	T1 – 2000+ gallons / 250 GPM T2 – 1000 to 1999 gallons / 250 GPM	All Wheel or 4 Wheel Drive Monitor Foam Proportioner
Heavy Equipment with Water	Tank Capacity Minimum Pump Flow (GPM)	Attributes
Pumper Cat	T1 – 200+ HP and min 500 gallons T2 – 100 to 199 HP and min 325 gallons T3 – 60 to 99 HP and min 200 gallons	Foam Proportioner Grapple Winch
Skidgine	T1 – 1200 + gallons / 50 GPM T2 – 800 to 1199 gallons / 50 GPM T3 – 400 to 799 gallons / 30 GPM T4 – 200 to 399 gallons / 30 GPM	Detachable Tank w/Grapple Foam Proportioner Grapple Winch Monitor
Softtrack	T1 – 170+ HP and min 600 gallons / 30 GPM	Foam Proportioner Winch Monitor
Heavy Equipment	Typing	Attributes
Dozer	T1 – 240+ HP min operating weight 60,000 pounds T2 – 150 to 250 HP min operating weight 35,000 pounds T3 – 99 to 165 HP min operating weight 20,000 pounds T4 – 50 to 110 HP min operating weight 10,000 pounds	Grapple Winch Ripper Low Ground Pressure

US Forest Service

Washington Office-Fire and Aviation Management

Incident Blanket Purchase Agreement (IBPA)

Fire Contract Program Administration

Excavator	T1 – Min 160 HP min operating weight 50,00 pounds T2 – Min 111 HP min operating weight 30,000 pounds T3 -Min 81 HP min operating weight 20,000 pounds T4 -Min 60 HP min operating weight 15,000 pounds	Steep Ground Excavator Clamshell Bucket Up Down Blade or Dozer Blade
Tractor Plow	T2 -Min 100 to 199 HP T3 -Min 50 to 99 HP	Grapple Winch Ripper Low Ground Pressure Plow Type (Standard Pull Behind, Swing Axle Pull Behind, Rear Tractor Mounted)
Transport	T1 -70,000+ weight loads T2 – 35,001-to-69,999-pound loads T3 – Up to 35,000-pound loads	None
Miscellaneous Heavy Equipment	Typing	Attributes
Feller Buncher	T1 – 226+ HP Minimum 20-inch SINGLE cut capacity T2 – 160 to 225 HP	Cab Leveling Carrier Type: (Tracked or Rubber Tired wheeled) Cutting Head Type: (Bar Saw, Rotating (Hot Saw) Disc) Harvester/Processing Head)
Mulcher/Masticator (Boom Mounted)	T1 – Min 160 HP min operating weight 50,000 pounds T2 – Min 111 HP min operating weight 30,000 pounds T3 – Min 81 HP min operating weight 20,000 pounds T4 – Min 60 HP min operating weight 15,000 pounds	Cab Leveling
Strip Mulcher/Masticator	T1 – 200 T2 – 100 to 199 HP T3 - 50 to 99 HP	Tracked or Rubber Tired
Skidder	T1 – 176 plus HP T2 – 100 to 175 HP T3 – 60 to 99 HP	Winch and Grapple Grapple Rubber Tired Steel Tracked

US Forest Service

Washington Office-Fire and Aviation Management

Incident Blanket Purchase Agreement (IBPA)

Fire Contract Program Administration

Road Grader	T1 – 165 plus HP T2 – 120 to 164 HP	14-foot Mol Board 4 wheel or All wheel Drive Rippers
Fallers		Attributes
Faller, Single	N/A	None
Faller, Module	2 Qualified Fallers	None
Trailers	Typing	Attributes
Clerical Support Unit	None	None
Communication Trailer	T1- Internet included in daily rate T2 – Internet is not included in daily rate	None
GIS Unit	T1 (4 computers, 6 workstations) T2 (2 computers, 4 workstations) T3 (1 computer, 5 workstations)	None
Helicopter Operations Support Trailer	None	None
Refrigerated Trailer	T1 – 43 feet plus T2 – 29 feet to 42 feet T3 – 24 feet to 28 feet	None
Other Equipment and Other Services	Typing	Attributes
Chipper	T1 – 18-inch min. diameter capacity T2 – 13-to-17-inch capacity T3 – 9-to-12-inch capacity	Boom Feed Self-Propelled
Crew Carrier Bus	None	None
Fuel Tender	T1 – 3501 plus gallons T2 – 2501 to 3500 gallons T3 – 500 to 2500 gallons T4- 600-900 gallons (200 Gal each tank) identify fuel in each tank	None
Mechanic W/Service Truck	Mechanic Heavy Mechanic Auto/Truck	None
Mobile Laundry Unit	T1 – 2500 pounds per day T2 – 1500 pounds per day	None
Mobile Sleeper Unit	T1 – 40 to 48 berths T2 – 21 to 39 berths T3 – 4 to 20 berths	None
Mobile Chainsaw Repair	None	None

US Forest Service

Washington Office-Fire and Aviation Management

Incident Blanket Purchase Agreement (IBPA)

Fire Contract Program Administration

Weed Washing Unit	All are currently listed as Type 1	None
<p align="center">Off Highway Vehicle (OHV)</p>	<p><u>Type 1</u> Min 2 Seats per Row Min 2 Rows of Seats Min Payload 1,000 pounds Min. Rear Box Capacity 500 pounds plus</p> <p><u>Type 2</u> Min 2 Seats per Row 1 Row of Seats Min. Payload 1,000 pounds Min Rear Box Capacity 500 pounds Plus</p> <p><u>Type 3</u> Min. 2 Seats per Row Min 2 Rows of Seats Min. Payload 800 Pounds Min. Rear Box Capacity 150 to 499 pounds</p> <p><u>Type 4</u> Min. 2 Seats per Row Min 1 Rows of Seats Min. Payload 800 Pounds Min. Rear Box Capacity 150 to 499 pounds</p>	<p align="center">None</p>
<p align="center">Vehicle with Driver</p>	<p>T1 Pickup – GVW 8,501 to 19,500 pounds 72” bed T2 Pickup – GVW 6,001 to 8,500 pounds min. 66” bed T3 Pickup – GVW up to 6,000 pounds min 60” bed Passenger Van 7 to 9 passengers SUV (Sport Utility Vehicle) Min. 5 passengers T1 Stakeside – GVW 14,001 to 26,000 pounds T2 Stakeside – GVW 10,001 to 14,000 pounds T3 Stakeside- GVWR 6,000 to 10,000 pounds</p>	<p align="center">All (4 wheel or All Wheel Drive) SUV (6 or more Passengers) Stakeside Only - Dump or Tilt Bed or Lift Gate</p>
<p align="center">Potable and Gray Water Truck(Tender) Handwashing Station (Trailer Mounted)</p>	<p align="center">Typing</p>	<p align="center">Attributes</p>
<p align="center">Gray Water Truck</p>	<p>T1 – 4,000 plus Gallons T2 – 2,500 to 3,999 Gallons T3 – 1,000 to 2,499 Gallons T4 – 400 to 999 Gallons</p>	<p align="center">Truck or Tractor Trailer Combo</p>

US Forest Service

Washington Office-Fire and Aviation Management

Incident Blanket Purchase Agreement (IBPA)

Fire Contract Program Administration

Potable Water Truck	T1 – 4,000 plus Gallons T2 – 2,500 to 3,999 Gallons T3 – 1,000 to 2,499 Gallons T4 – 400 to 999 Gallons	Truck or Tractor Trailer Combo
Hand Wash (Trailer Mounted)	T1 – 12 plus Sinks T2 – 8 to 12 Sinks	None
Emergency Medical Services	Typing	Attributes
Ambulance	Advanced Life Support (ALS): T1 - EMT& EMT-P (Minimum) and capable of Hazmat Response/Transport T2 – EMT & EMT-P (Minimum) Basic Life Support (BLS): T3 – EMTx2 (Minimum) and capable of Hazmat Response/Transport T4 – EMTx2 (Minimum) *Must have equipment required in the state that they are servicing, follow their medical direction, protocols, and all laws/requirements specific to the state in which the contractor is providing service while “under hire.”	Four Wheel or All Wheel Drive Fireline Qualified Personnel
EMR (Emergency Medical Responder)	Fireline: EMTF AEMF EMPF Non Fireline: EMTB AEMT EMTP	None

US Forest Service
 Washington Office-Fire and Aviation Management
 Incident Blanket Purchase Agreement (IBPA)
 Fire Contract Program Administration

Rapid Extraction Module Support (REMS)	<p><u>Type 1</u> 4 Medical Personnel ALS Only 2 - Rope Rescue Technicians 2 - Rope Rescue Operations 1 - Paramedic & 1 EMT (not to be used as EMPF/EMTF) 1-2 - 4x4 Vehicle w/Extraction Equipment (no AWD) 1 - 4X4 OHV w/ROPS, trailer, patient transport, DOT helmets</p> <p><u>Type 2</u> 4 - Medical Personnel ALS or BLS 2 - Rope Rescue Technicians 2 - Rope Rescue Operations 2 EMTs (BLS to be used EMTF), ALS provider acceptable but not required 1 - 4x4 Vehicle (no AWD) 1 - 4X4 OHV w/ROPS, trailer, patient transport, DOT helmets</p> <p><u>Type 3</u> 2 – Medical Personnel ALS or BLS 1 - Rope Rescue Technicians 1 - Rope Rescue Operations 1 - Paramedic (ALS) or 1 EMT (BLS) 1 - 4x4 Vehicle (no AWD) 1 - 4X4 OHV w/ROPS, trailer, patient transport, DOT helmets</p>	<p>Type 1 ALS only Type 2 and 3 ALS or BLS</p>
---	---	---

Regional VIPR IBPA Resources			
Region	Resource	Typing	Additional Resource Attributes
1,4 and 6	Heavy Equipment Task Force	None	None
5	Incident Base Unit	T1 – 10 Trailers,4 Tents T2 – 5 Trailers, 2 Tents	None

US Forest Service
 Washington Office-Fire and Aviation Management
 Incident Blanket Purchase Agreement (IBPA)
 Fire Contract Program Administration

At Incident Management Support (AIMS) IBPA Resource		
Resource	Typing	Additional Attributes
Tents	T1 – 1,001 to 1,300 square feet, 10 outlets min. T2 – 701 to 1,000 square feet, 10 outlets min. T3 – 501 to 700 square feet, 8 outlets min. T4 – 200 to 500 square feet, 6 outlets min.	None
Portable Toilet and Handwash Stations	None	None
Log Loader	T1 – Min. 175 hp and above T2 – Min. 105 hp to 174 hp	Steel Tracked Rubber Tired
Log Processor	None	Steel Tracked Rubber Tired Trailer Mounted
Log Truck	Type 1 – 3 plus axels 80,000 pound or more GVW Type 2 – Tandem (2) axels. GVW up to 79,999 pounds.	Self-Loader Long Log Mule Train Short Log
Forwarder	Type 1 – 200 plus hp Type 2 – 150 to 199 hp Type 3 – 100 to 149 hp	Wheeled Steel Tracked

Abbreviations Commonly Associated with Equipment:	
GPM- Gallons Per Minute	AWD- All Wheel Drive
HP- Horsepower	GVW- Gross Vehicle Weight
Min/Max- Minimum or Maximum	ALS- Advanced Life Support
BLS- Basic Life Support	EMT- Emergency Medical Technician
EMTP- Emergency Medical Technician Paramedic	EMTB- Emergency Medical Technician Basic
AEMT-Advanced Emergency Medical Technician	EMTF- Emergency Medical Technician Fireline
AEMF- Advanced Emergency Medical Technician Fireline	EMPF- Paramedic Fireline
Sq Ft-Square Feet	UTV- Utility Task Vehicle
CC- Cubic Centimeters	ATV- All Terrain Vehicle
OHV-Off Highway Vehicle	CAFS- Compressed Air Foam System